

Product Data Sheet

WTXH watttrixHub

Extension for heating systems



Hardware Parameters

Mechanical and Electrical Specifications

Power Supply	24 V DC / 2 A
Dimensions	Appr. 70 x 47 x 138 mm (HxLxD)
Mounting type	Top-hat rail mounting (35 mm, 2 HE)
Terminal blocks grid dimension for supply plug	3.81 mm
Weight	450 g
Max. power consumption	Appr. 10 W
Ambient temperatures	From 10 °C to 40 °C
Relative humidity	Between 30 % and 60 %

Connectors

Ethernet	1x LAN 10/100/1000 MBit/s
Heater Connection Ports	6x RS-485 - up to 350 heating pixels per connection
Digital Out	2x (24 V open-collector)
Digital In	2x (24 V open-collector, isolated)

Explore our products related to the watttrixHub:

watttrixServer Performance



control-unit and communication interface



Gateway between cera2heat® or cera2seal® heating systems and PLC




Interface to watttrix Digital Services



Host of graphical user interface for control and monitoring

watttron Heater



Digital Heating System designed for sealing and thermoforming applications

Contact us for more information

watttron Inc.

150 N Michigan Ave 35th Floor – Chicago, IL 60601

+1 (312) 665-0984

sales@watttron.com

www.watttron.com